



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

EQUIPMENT



T5

WALK-BEHIND FLOOR SCRUBBER-DRYER

- Increase safety with NFSI-certified¹ ec-H₂O NanoClean™ cleaning technology or FaST® Foam Scrubbing Technology
- Quietly clean with an OSHA-recognised test-standard 67 dBA
- Achieve complete solution recovery – even on 180 degree turns – with superior squeegee design

REACH A HIGHER LEVEL OF **CLEANLINESS**,
HEALTH, AND **SAFETY** WITH THE NEW,
ENVIRONMENTALLY FRIENDLY T5.



REDUCE DEPENDENCY ON CLEANING CHEMICALS

Scrub chemical-free with ec-H₂O NanoClean™ cleaning technology².

DECREASE NOISE LEVELS

Quietly scrub noise-sensitive environments with the T5's OSHA-recognised 67 dBA.

IMPROVE SAFETY

Increase safety and clean effectively with chemical-free ec-H₂O NanoClean™ technology or FaST Foam Scrubbing Technology. The T5 uses up to 70% less water with both technologies. ec-H₂O NanoClean™ uses no detergent. FaST uses up to 90% less detergent than traditional scrubber-dryers.

MOVE FROM CLEANLINESS TO SANITISATION

Reduce scrubber-dryer mould and bacteria to ensure the highest level of cleanliness with complete-access Hygenic® tanks.

HIGH PRODUCTIVITY WITH GEL BATTERIES

Achieve up to 3.5 hours of run-time with environmentally preferable sealed batteries.

MAXIMISE FLEXIBILITY AND VERSATILITY

Choose from 600, 700, 800 mm disk or 650, 800 mm cylindrical brushes for scrubbing a variety of spaces and applications.

CONSISTENT CLEANING RESULTS

Lock-in consistent, repeatable cleaning results with exclusive QA Controls™ system.

INSIDE THE T5



- A** Easily train new operators to use the simple, intuitive controls.
- B** Scrub for up to 150 minutes on a single tank – 70% longer than any other comparable machine – when you equip the T5 with ec-H2O NanoClean™ or FaST technology.
- C** Reduce operator contact with waste water and prevent clogged hoses/drains with the convenient debris tray.
- D** Eliminate the need for follow-up passes and mop-ups with the fully self-adjusting splash skirt that captures 100% of scrub deck overspray.

- E** Quickly remove and replace brushes and squeegees. Plus, with the “no hassle” squeegee system, there are no tools for maintenance and the blade is factory set at the optimum recovery angle.
- F** Solution and recovery tanks easily cleanable. Exclusive Hygenic® tanks are fully accessible for sanitisation.
- G** Save time and storage space with the on-board charger.

EXCLUSIVE TECHNOLOGIES


(optional cleaning innovations)

All technologies increase scrub time up to three times using a single tank of water.



Electrically converted water is created by an onboard e-cell that generates millions of microscopic bubbles known as nanobubbles that promote the cleaning efficacy of the solution.

This next generation solution now cleans better and cleans more soils in more applications, thanks to the nano-scale bubbles that are an important part of the cleaning mechanism.



FaST® Foam Scrubbing Technology uses up to 70% less water and 90% less chemicals to improve floor traction as certified by NFSI, helping reduce the risk of slip and fall accidents.

¹ Check applicable regulations in your market. NFSI is a private US-based not-for-profit group dedicated to reducing slip-and-fall accidents. Certification under the ANSI/NFSI B101.1-2009 Test Method for Measuring Wet SCOF of Common Hard-Surface Floor Materials available at <http://www.nfsi.org/>.

² ec-H2O NanoClean™ technology is not designed for all soils, including heavy concentrations of fats and oils. Conventional chemical cleaners may be required for those soils.

ENVIRONMENTAL STEWARDSHIP



ec-H2O NanoClean™ and FaST technologies are NFSI (National Floor Safety Institute) Certified. NFSI certification ensures a product has passed a 2-phase testing process, proving the floor product helps to reduce potential for slip-and-fall accidents.



ec-H2O NanoClean™ and FaST technologies are registered by NSF International. NSF International is an independent, not-for-profit organisation that ensures formulation and labels on these products meet appropriate food safety regulations.



Tennant FaST 365 and FaST 965 detergents have been awarded the European Eco-label. This proves that our Tennant FaST detergents have a reduced environmental impact compared to standard detergents



Conserve Resources



Reduce Detergents



Increase Safety



Improve Air Quality



Reduce Noise

GENUINE TENNANT PARTS, SUPPLIES AND SERVICE

Tennant Service Offering

- Maximise safety, productivity and uptime
- Control and protect your investment and lower your total cost of ownership
- Benefit from over 200 factory-trained service technicians across Europe

Tennant Parts & Supplies

- Operate your machine with confidence
- Benefit from years of worry-free operation

Tennant Cleaning Solutions

- Further your sustainable cleaning goals
- Choose sustainable benefits your company wants

T5 WALK-BEHIND FLOOR SCRUBBER-DRYER

SCRUBBING SYSTEM

	DISK	CYLINDRICAL
Cleaning path	600 mm 700 mm 800 mm	650 mm 800 mm
Solution tank capacity	85 L	85 L
Productivity (per hour)		
Theoretical max	2500 m ² 2900 m ² 3300 m ²	2700 m ² 3300 m ²
Estimated actual* (conventional)	1660 m ² 1900 m ² 2200 m ²	1790 m ² 2200 m ²
Estimated actual* (ec-H2O NanoClean™ or FaST®)	1900 m ² 2100 m ² 2400 m ²	2000 m ² 2400 m ²
Scrub motors	0.56 kW	0.47 kW
Scrub motor speed	220 rpm	1500 rpm
Brush/pad down pressure		(3 settings) 18, 36, 54 kg

RECOVERY SYSTEM

Recovery tank capacity (includes demisting chamber)	102 L
Vacuum motor	0.64 kW, 3-stage
Waterlift	1570 mm

BATTERY SYSTEM

System Voltage	24 V (4x 6V batteries), charger included
Standard run time**	6V 200Ah (C5) / up to 4.5h
Optional sealed run time**	6V 180 Ah (C5) / up to 3.5h
Gradeability (ramp climb)	
Scrubbing/transporting (full)	3.0° / 5.0°
Trailer ramps (empty)	11°

PROPELLING & POWER SYSTEM

Propel speed (variable to)	
Transport	4.3 km/h
Scrubbing	4.0 km/h

MACHINE SPECIFICATIONS

Product length	1340 mm 1410 mm 1480 mm	1410 mm 1410 mm
Product width (scrub head)	640 mm 740 mm 840 mm	710 mm 860 mm
Squeegee width	910 mm 1050 mm 1180 mm	1050 mm 1180 mm
Product height		1120 mm
Product weight (with batteries)	263 kg 276 kg 282 kg	282 kg 285 kg
Sound level***		68 dBA

WARRANTY

See your local representative for warranty information.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on continuous scrubbing run times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment manufacturers & OSHA.

Specifications subject to change without notice.

SEEING IS BELIEVING

For a demonstration or additional information contact us:

TENNANT UK CLEANING SOLUTIONS LTD

Gladstone Road
Northampton NN5 7RX
UNITED KINGDOM
Tel: 0800 111 4402 (local rate UK only)
Tel: 01604 583191
Fax: 0845 052 9349
E-mail: sales.uk@tennantco.com
E-mail: enquiries@tennantco.com

TCS EMEA GmbH

Sommerfeld 1
5202 Neumarkt am Wallersee
AUSTRIA
Tel: +43 (0)6216 4524 & 4525
Fax: +43 (0)6216 4524 20
E-mail: office@tennant-cee.com

TENNANT EUROPE NV

Roderveldlaan 3
2600 Antwerp
BELGIUM
Tel: +32 3 217 94 11
Fax: +32 3 217 94 19
E-mail: europe@tennantco.com